

ROYSON ENGINEERING COMPANY

CENTRIFUGAL TUMBLING MACHINE

100 N. PENN ST. HATBORO, PA. 19040 PH#215-675-2800 FAX#215-675-3035
BULLETIN #1237



CTB-30

- HIGH SPEED FINISHING. 30 TIMES FASTER THAN ROTARY BARRELS.
- (4) REMOVABLE HEXAGONAL BARRELS.
- VERY QUIET OPERATION.
- STANDARD THREE PHASE POWER
- HEAVY STEEL CONSTRUCTION
- ROYSON MACHINE WARRANTY

MACHINE FEATURES:

1. (4) BARRELS WITH HOT POUR URETHANE DROP IN LINERS. REMOVABLE LIDS. BARRELS ARE LOCKED IN PLACE WITH HEAVY CLAMP BAR. 0-180 RPM BARREL SPEED. .25 CU/FT BARREL CAPACITY . BARREL DIMENSION 7"W X 12"L
2. ELECTROMAGNETIC DOOR LOCK. DOOR CAN NOT BE RAISED WHEN MACHINE IS RUNNING. MACHINE WILL NOT START WHEN DOOR IS RAISED.
3. BARREL JOG. ONCE DOOR IS RAISED, BARRELS CAN BE JOGGED INTO POSITION FOR UNLOADING.
4. 2 HP, 208/240/460/3/60 POWER.
5. MACHINE DIMENSIONS: 45"W X 35"FRONT TO BACK X 51"H
6. MACHINE WEIGHT: 975 LBS.
7. CONTROL PANEL BOLTED TO MACHINE BASE. PANEL INCLUDES VARIABLE SPEED DRIVE, ON/OFF BUTTONS, JOG BUTTON, TIMER.
8. DURABLE EPOXY MACHINE ENAMEL PAINT.

COPYRIGHT ROYSON 2010